

Typesetting Articles for *Res Philosophica*^{*}[†]

Boris Veytsman[‡]

2015/11/14, v1.28

Abstract

This package provides a class for typesetting articles for the journal *Res Philosophica*, <http://www.resphilosophica.org>.

Contents

1	Introduction	2
2	User Interface	2
2.1	Commercial Fonts	2
2.2	Invocation and Options	2
2.3	Topmatter	3
2.3.1	Commands for Authors	3
2.3.2	Commands for Editors	5
3	Special Notes	6
3.1	Bibliography	6
4	Implementation	9
4.1	Options	9
4.2	Loading Classes and Packages	11
4.3	Page Dimensions and Paragraphing	12
4.4	Headers	12
4.5	Top Matter Macros	14
4.6	Typesetting Top Matter	18
4.7	Notes	21
4.8	Typesetting End Matter	21
4.9	Sectioning	22
4.10	Additional Commands	23
4.11	The End	24

^{*}©2012, Boris Veytsman

[†]This work was commissioned by the Saint Lois University

[‡]borisv@lk.net, boris@varphi.com

1 Introduction

According to the statement at <http://www.resphilosophica.org/>, *Res Philosophica* is an international, quarterly journal of philosophy that publishes research in all areas of philosophy, historical and topical. Founded as *The Modern Schoolman* by Jesuit Scholastics in 1925, the journal is edited by members of the Philosophy Department at Saint Louis University and supported generously by the College of Arts and Sciences.

This package is intended for the authors and editors of the journal to typeset the articles in L^AT_EX. Note that the journal is typeset in *Linotype Sabon*,. The users may buy the fonts and install their free L^AT_EX support [1], or use the options `bodyfont=cm` and `rpfnt=cm` to typeset the articles using Computer Modern. Of course, the line and page breaks in the latter case are different from those in the final version typeset with commercial fonts.

2 User Interface

2.1 Commercial Fonts

The package can be used with free Computer Modern fonts or with commercial fonts to mimick the journal typesetting. The installation of additional fonts is therefore fully optional.

Res Philosophica uses Linotype Sabon for the body text and URW Garamond for mathematics. Sabon is a commercial font. URW Garamond is free, but due to license restrictions it is usually not included with T_EXLive, MikT_EX and other major distributives. If you bought Linotype Sabon, you need to install the package `lsabon` [1]. To use URW Garamond, you need to download the `pfb` files from a CTAN mirror (<http://mirror.ctan.org/fonts/urw/garamond/>), install them in the directory `fonts/type1/urw/garamond` under `$TEXMFLOCAL` and run `texhash`.

2.2 Invocation and Options

To use the class put in the preamble of your document

```
\documentclass[<options>]{resphilosophica}
```

The class `resphilosophica` internally loads `amsart`, and therefore all class options for `amsart` are technically valid. However, most of them are not especially meaningful for `resphilosophica`. There are several options specific for this class. They are described below. Note that the class uses key-value interface for some options, for example

```
\documentclass[bodyfont=sabon]{resphilosophica}
```

option
`bodyfont` The option `bodyfont` can have three values: `sabon` for Sabon/Garamond fonts,

`cm` for Computer Modern and `auto` (default). The later option switches to the use of Sabon if the font metrics are present in your system, and to the use of Computer Modern otherwise.

option
`manuscript` The option `manuscript` is intended to facilitate the communications between the editor and the author. It enables two things:

1. The numbering of lines in the manuscript is switched off in the normal mode, but is on in the manuscript mode.
2. The command `\EditorialComment` is no-op in normal mode, but produces marginal commentaries in the manuscript

option
`preprint` The option `preprint` is for the final version of the manuscript. In this mode there are no editorial comments, but the numbering of lines is preserved

option
`screen` The option `screen` is intended for the screen reading. When this option is selected, the links become highlighted.

option
`forthcoming`
`\onlinedate` The option `forthcoming` is like `screen`, but it is used when there is no information about the volume. The macro `\onlinedate{\langle date \rangle}` can be used to set the date of online publication.

option
`natbib` The preferred solution for bibliography is `natbib` package [2]. The option `natbib=true` (default) sets the package and the proper options, including bibliography style. The option `natbib=false` switches this behavior off, and the formatting of the bibliography becomes the full responsibility of the author. The package includes the BibTEX bibliography style `resphilosophica bst`.

2.3 Topmatter

Topmatter is the part of the article with the informations about the authors, their affiliations, the publication data, etc.

There are two kinds of top matter commands: the ones used primarily for authors and the ones used primarily for editors. We describe them separately.

2.3.1 Commands for Authors

`\title` The command `\title`, as in `amsart` class, has two arguments: one optional, and one mandatory:

`\title[\langle ShortTitle \rangle]{\langle FullTitle \rangle}`

The mandatory argument is the full title of the article. The optional argument, if present, defines the shorter version of the title for running heads. If the optional argument is absent, the full title is used instead.

The title is typeset in small caps. The result of the command `\emph` in title depends on whether commercial fonts and the package `lsabon` package is used: with a relatively recent version of the package `lsabon` the emphasized text is typeset in Small Caps Italics.

`\author`
`\email`
`\address`
`\curraddr`
`\urladdr` The interface for specifying the authors and their affiliations is close to the one of `amsart` [3] (and different from the standard L^AT_EX). For each author a

separate command `\author` should be used, followed by `\address` and (optionally) `\curraddr`, `\email` and `\urladdr`.

`\shortauthors`

In some cases the authors list may be too long for the running head, even if the abbreviated forms are used for each author. In this case it is possible to change the running head by a *redefinition* of the command `\shortauthors`. This redefinition must be done after all `\author` commands, but before `\maketitle`:

```
\renewcommand{\shortauthors}{A.~Smith et al}
```

`\thanks`

Like `amsart` (and unlike standard L^AT_EX), `resphilosophica` allows `\thanks` only *outside* of commands `\title` and `\author`. The text of `\thanks` is typeset at the end of the paper as a footnote marked ‘Acknowledgements’. Note that the right vertical positioning of this footnote might require an additional run of L^AT_EX.

`\titlenote`

The `\titlenote{<note>}` command creates a special footnote for the title. This command should be issued *outside* the `\title` command.

`\authornote`

The similar `\authornote{<note>}` command creates a special footnote for the author. This command should be issued *outside* the `\author` command.

`\copyrightnote`

Normally each paper is copyrighted by the authors and by the journal. This is reflected in the footnote on the first page of the article. However, by arrangement with the editors, certain papers may have different copyright. The command `\copyrightnote{<copyright statement>}`, if issued, changes the footnote to the corresponding text, for example:

```
\copyrightnote{\textcopyright~2012 by the authors. This paper may  
be reproduced, in its entirety, for noncommercial purposes.}
```

Note that if you issue this command, you should explicitly include both the copyright sign and the year unless the paper does not have a copyright, for example:

```
\copyrightnote{This paper is in the public domain}
```

`\copyrightyear`

Normally the copyright statement includes the year of copyright, which is assumed to be the publication year as specified by the `\publicationyear` command (see below). If this assumption is wrong, you may correct it, for example,

```
\copyrightyear{1998}
```

`\abstract`

The abstract of the paper must be put between `\begin{abstract}` and `\end{abstract}`. Unlike the situation in `amsart` class, abstract may be put *after* `\maketitle`.

`\maketitle`

The macro `\maketitle` typesets the top matter. All top matter information should be specified before this command.

2.3.2 Commands for Editors

The commands described in this section should be used by the editors to insert the information about the published paper. They must be put before the `\maketitle` command.

```
\volumenumber  
  \issuenumber  
  \publicationyear  
  \publicationmonth  
    \papernumber  
    \startpage  
    \endpage  
      \volumenumber{88}  
      \issuenumber{1--2}  
      \publicationyear{2012}  
      \publicationmonth{January--February}  
      \papernumber{2}  
      \startpage{1}  
      \endpage{39}
```

Note that if the argument of `\endpage` is empty, L^AT_EX tries to calculate the last page number as best as it can.

Sometimes publication month for double issues is too long to fit on the back cover. For this case `\publicationmonth` has the optional argument, abbreviated month, for example

```
\publicationmonth[Jan--Feb]{January--February}
```

`\doinumber` Normally you do not need to set the DOI of the paper: T_EX will construct the number using the paper data (including paper number in the current issue). However, you *may* override its decision using the command `\doinumber` which sets the DOI explicitly, for example, `\doinumber{(10.11612/resphilosophica.2013.01.01)}`. You probably should not use this macro.

`\prevpaper` Instead of setting `\startpage`, one can use the the command `\prevpaper{<previous paper>}`, with the argument being the location and file name of the previous paper in the journal, for example:

```
\prevpaper{../infinity/concept_of_infinity}
```

Note that the `.tex` suffix should *not* be used. The previous paper must be processed by `latex` prior to the current one. In this case `latex` will read the last page of the previous paper, and start the current one from the proper page number.

`\paperUrl` When a paper is submitted to the Crossref service, which keeps the database of Digital Object Identifiers, its URL is calculated by the script used by editors. The command `\paperURL{<url>}` overrides this choice.

The macro `\EditorialComment[<level>]{<comments>}` typesets the comments on the margins in the `manuscript` mode, for example,

```
Which is a well known fact.\EditorialComment{A citation is  
needed}\EditorialComment[1]{Please make the citation more  
explicit}.
```

Editorial comments have *levels*. A level can be numeric or symbolic; symbolic levels can contain letters and numbers. The default level is 0, so `\EditorialComment{text}` is equivalent to `\EditorialComment[0]{text}`.

`\ECSelect` The command `\ECSelect{<level>,...}` selects the levels of editorial comments to display in the manuscript mode. Note that 0 corresponds to the default level, so the command `\ECSelect{0}` should be used to show these comments.

Sometimes it is useful to tell the author about typesetter's changes in the manuscript. The dialog between the author and typesetter might take several iterations, so the class provides a system for this dialog.

`\TC` The macro `\TC[<level>]{<text>}` makes `{<text>}` highlighted in the `manuscript` mode if the level `[<level>]` is chosen. For example,

```
This proposition \TC[1]{(first discussed by the author in 2010)} can  
be stated as the following.
```

The level can be numerical, or logical, e.g. `\TC[new]{text}`. Actually any combination of letters and numbers that does not contain commas or spaces can be used for level. By default the level is 0, so `\TC{<text>}` is equivalent to `\TC[0]{<text>}`.

`\TCSelect` The decision to highlight certain levels is done by the command `\TCSelect[<color>]{<level>,...}`. The first optional argument is the color used for highlighting; by default `magenta`. Actually any color expression understandable by `xcolor` can be used. The second argument is a comma-separated list of levels that will be highlighted by the selected color. The command `\TCSelect` can be repeated, for example,

```
\TCSelect{0,1,new}  
\TCSelect[blue]{second-level}
```

If a level does *not* appear in any `\TCSelect` command, it is not highlighted—that is why we do not need a separate `\TCOff` command.

3 Special Notes

`notes` Some authors include special notes, for example, bibliography description, that precede list of references, but follow the signature block. The environment `notes` is intended for this purpose. It has one mandatory argument, title, for example

```
\begin{notes}{Bibliography notes}  
The best discussion of the problem can be found in...  
\end{notes}
```

3.1 Bibliography

As mentioned above, `resphilosophica` by default uses `natbib` [2]. You should use `natbib` commands like `\citet`, `\citep` etc.

Note that `\bibliographystyle` command should *not* be issued by the author: the package takes care of this. You just need to type

```
\bibliography{DATABASE, DATABASE...}
```

The bibliography style used for the articles is `resphilosophica.bst`. Compared to standard styles it has two additional fields:

doi: DOI number of the publication. Write there only the number: the style will automatically add <http://dx.doi.org> and make the reference clickable.

titlenote: the note that should be put after the title rather than at the end of the entry¹, for example, the information about translators, editors of critical editions, etc:

```
@book{Knuth94:TheTeXbook,
  address = {Reading, MA},
  author = {Knuth, Donald Ervin},
  titlenote = {Illustrations by Duane Bibby},
  publisher = {Addison-Wesley Publishing Company},
  series = {Computers \& Typesetting A},
  title = {The \TeX book},
  year = {1994},
}
```

- | | |
|--|--|
| <code>\enquote</code>
<code>\ensquote</code>
<code>\suppresscomma</code> | <p>The macros <code>\enquote</code> and <code>\ensquote</code> put their arguments in double and single quotes correspondingly. They are used to suppress unwanted commas and periods inside bibliography entries.</p> <p>Sometimes BibTeX inserts an unwanted comma into an entry, for example, in the following one:</p> |
|--|--|

```
@incollection{ande97a,
  Address = {Macon, GA},
  Author = {Anderson, Thomas C.},
  Booktitle = {Concluding Unscientific Postscript to
\enquote{Philosophical Fragments},},
  Date-Modified = {2013-09-04 21:27:17 +0000},
  Editor = {Robert Perkins},
  Owner = {Andrew},
  Pages = {187--204},
  Publisher = {Mercer University Press},
  Series = {International Kierkegaard Commentary},
  Timestamp = {2013.09.04},
  Title = {Kierkegaard and Approximation Knowledge},
  Volume = {12},
```

¹This field was proposed by Maureen Shupsky for the *Annals of Mathematics* bibliography style.

```
Year = {1997}}
```

The command `\suppresscomma` suppresses the next comma:

```
Booktitle = {Concluding Unscientific Postscript to  
\enquote{Philosophical Fragments},\suppresscomma},
```

The bibliography style has a special entry type, `inloosecollection`. It resembles the standard `incollection` entry, but it refers to a collection of papers written by separate authors that are quoteable separately as an independent entity. This entry is typeset slightly differently than the standart `incollecttion` entry.

`\AddtoEndMatter`
If you decide to forgo `natbib`, you can use `natbib=false` option. Then you should remember to put the bibliogrtaphy *after* the end matter (authors' addresses etc) using the command `\AddtoEndMatter`:

```
\AddtoEndMatter{MY BIBLIOGRAPHY COMMANDS}
```

Acknowledgements

This package was commissioned by the journal *Res Philosophica* and funded by Saint Louis University. I am grateful to Jonathan Jacobs for tireless testing of the package.

4 Implementation

4.1 Options

We need `xkeyval` since some of our options may have values:

```
1 \RequirePackage{xkeyval}
```

`\ifRESP@fontauto` First, check whether the user have the body font explicitly configured:

```
2 \newif\ifRESP@fontauto
3 \RESP@fontautotrue
```

`\ifRESP@rpfontauto` Same for *Res Philosophica* font

```
4 \newif\ifRESP@rpfontauto
5 \RESP@rpfontautotrue
```

`\ifRESP@lsabon` Are we using linotype sabon?

```
6 \newif\ifRESP@lsabon
7 \RESP@lsabonfalse
```

`\ifRESP@mtshadow` Are we using MT Imprint Shadow?

```
8 %\newif\ifRESP@mtshadow
9 %\RESP@mtshadowfalse
```

`bodyfont` And the option to check the user input:

```
10 \define@choicekey**+{resphilosophica.cls}{bodyfont}[\val\nr]{auto,
11   sabon, lsabon, cm}[auto]{%
12   \ifcase\nr\relax
13     \RESP@fontautotrue
14   \or
15     \RESP@fontautofalse
16     \RESP@lsabontrue
17   \or
18     \RESP@fontautofalse
19     \RESP@lsabontrue
20   \or
21     \RESP@fontautofalse
22     \RESP@lsabonfalse
23 \fi}{%
24 \PackageWarning{resphilosophica}{The option bodyfont must be auto,
25   sabon or cm. Using auto}\RESP@fontautotrue}
```

`rpfont` And the option to check the user input:

```
26 % \define@choicekey**+{resphilosophica.cls}{rpfont}[\val\nr]{auto,
27 %   imprint, imprintshadow, cm}[auto]{%
28 %   \ifcase\nr\relax
29 %     \RESP@rpfontautotrue
30 %   \or
31 %     \RESP@rpfontautofalse
32 %     \RESP@mtshadowtrue
```

```

33 %   \or
34 %     \RESP@rpfontautofalse
35 %     \RESP@mtshadowtrue
36 %   \or
37 %     \RESP@rpfontautofalse
38 %     \RESP@mtshadowfalse
39 %   \fi}%%
40 % \PackageWarning{resphilosophica}{The option rpfont must be auto,
41 %   imprintshadow or cm. Using auto}\RESP@rpfontautotrue}

natbib Checking natbib option:
42 \define@boolkey+{resphilosophica.cls}[RESP@]{natbib}[true]{}{%
43   \PackageWarning{resphilosophica}{The option natbib must be
44   yes or no. Using yes}}
45 \RESP@natbibtrue

The size-changing options produce a warning:
46 \long\def\RESP@size@warning#1{%
47   \ClassWarning{RESPart}{Size-changing option #1 will not be
48   honored}}%
49 \DeclareOptionX{8pt}{\RESP@size@warning{\CurrentOption}}%
50 \DeclareOptionX{9pt}{\RESP@size@warning{\CurrentOption}}%
51 \DeclareOptionX{10pt}{\RESP@size@warning{\CurrentOption}}%
52 \DeclareOptionX{11pt}{\RESP@size@warning{\CurrentOption}}%
53 \DeclareOptionX{12pt}{\RESP@size@warning{\CurrentOption}}%

\ifRESP@manuscript Manuscript mode:
54 \newif\ifRESP@manuscript
55 \RESP@manuscriptfalse
56 \DeclareOptionX{manuscript}{\RESP@manuscripttrue}

\ifRESP@screen Screen mode:
57 \newif\ifRESP@screen
58 \RESP@screenfalse
59 \DeclareOptionX{screen}{\RESP@screentrue}

\ifRESP@preprint Whether we are in the preprint mode
60 \newif\ifRESP@preprint
61 \RESP@preprintfalse
62 \DeclareOptionX{preprint}{\RESP@preprinttrue}

\ifRESP@forthcoming Whether we are in the forthcoming mode
63 \newif\ifRESP@forthcoming
64 \RESP@forthcomingfalse
65 \DeclareOptionX{forthcoming}{\RESP@forthcomingtrue}

All other options are passed to amsart:
66 \DeclareOptionX{*}{\PassOptionsToClass{\CurrentOption}{amsart}}
And executing options:
67 \ProcessOptionsX

```

4.2 Loading Classes and Packages

We use `amsart` since it has nice features for front matter:

```

68 \LoadClass[noamsfonts,twoside]{amsart}
    Some packages
69 \RequirePackage{microtype, fancyhdr, xcolor, lastpage, collect}
70 \RequirePackage[bottom,multiple]{footmisc}
71 \RequirePackage[hyperfootnotes=false]{hyperref}
72 \urlstyle{rm}
73 \ifRESP@manuscript\hypersetup{colorlinks,allcolors=blue}\else
74   \ifRESP@screen\hypersetup{colorlinks,allcolors=blue}\else
75     \ifRESP@preprint\hypersetup{colorlinks,allcolors=blue}\else
76       \ifRESP@forthcoming\hypersetup{colorlinks,allcolors=blue}\else
77         \hypersetup{hidelinks}\fi\fi\fi\fi

```

The font to use depends on the options. Note that L^AT_EX cannot reliably determine whether a binary file like `SabonLTRom.pfb` exists in the system, so we check for the `.fd` file instead (sigh):

```

78 \ifRESP@fontauto
79   \IfFileExists{t1lsb.fd}{\RESP@lsabontrue}{\RESP@lsabonfalse}\fi

```

If the user wants, we load Sabon and URW Garamond. Note that `mathdesign` defines `sc` to be `fsc`, so we need to redefine it for Sabon. Also, it defines `b` to `mb`, so we redefine it again.

```

80 \ifRESP@lsabon
81   \RequirePackage[mdugm]{mathdesign}
82   \RequirePackage[rmdefault]{lsabon}
83   \renewcommand\scdefault{sc}
84   \renewcommand{\bfdefault}{b}
85 \fi

```

Checking the existence of `miih` font metrics:

```

86 %\ifRESP@rpfontauto
87 %  \IfFileExists{t1miih.fd}{\RESP@mtshadowtrue}{\RESP@mtshadowfalse}\fi

```

`\rpdefault` This is the font for *Res Philosophica*:

```

88 %\ifRESP@mtshadow
89 %  \def\rpdefault{miih}\else
90 %  \def\rpdefault{\rmdefault}\fi

```

`\AddtoEndMatter` A syntax sugar to add something after signature:

```

91 \def\AddtoEndMatter#1{\g@addto@macro\enddoc@text{#1}}

```

And loading natbib:

```

92 \ifRESP@natbib
93   \RequirePackage[round]{natbib}
94   \AtEndDocument{\bibliographystyle{resphilosophica}}
95   \let\RESP@bibliography=\bibliography
96   \def\bibliography#1{\AddtoEndMatter{\RESP@bibliography{#1}}}
97   \def\bibsection{\par\addpenalty\@secpenalty\addvspace{\bigskipamount}%

```

```

98      \noindent \Small References:\par\nobreak\vskip\medskipamount\@afterheading}
99  \def\bibfont{\Small}
100 \fi

```

4.3 Page Dimensions and Paragraphing

```

\pdfpaperwidth Paper:
\pdfpaperheight 101 \ifRESP@manuscript\else
102 \AtBeginDocument{\setlength{\pdfpagewidth}{432bp}\%
103 \setlength{\pdfpageheight}{648bp}}
104 \fi

\textheight The size of the type block:
\textwidth 105 \setlength{\textheight}{318pt}
106 \setlength{\textwidth}{540pt}

\evensidemargin The margins:
\oddsidemargin 107 \setlength{\evensidemargin}{-10pt}
108 \setlength{\oddsidemargin}{-26pt}
109 \ifRESP@screen
110 \setlength{\evensidemargin}{-18pt}
111 \setlength{\oddsidemargin}{-18pt}
112 \fi
113 \ifRESP@forthcoming
114 \setlength{\evensidemargin}{-18pt}
115 \setlength{\oddsidemargin}{-18pt}
116 \fi

\topmargin Top margin
117 \setlength{\topmargin}{-48pt}

\listsep This is the space around lists. amsart defines it as \smallskipamount. We slightly
increase it:
118 \listsep\medskipamount

```

4.4 Headers

```

\headsep Separation between the header and the body
119 \setlength{\headsep}{14pt}

\headheight The height of the headers:
120 \setlength{\headheight}{12pt}

\headrulewidth We do not want decorative rules in the journal:
\footrulewidth 121 \renewcommand{\headrulewidth}{0pt}
122 \renewcommand{\footrulewidth}{0pt}

```

```

\footskip Separation between the footer and the body
123 \setlength{\footskip}{20pt}

\RESP@printlinecount Do we want to print line count?
124 \newif\ifRESP@printlinecount
125 \RESP@printlinecountfalse
126 \ifRESP@manuscript\RESP@printlinecounttrue\fi
127 \ifRESP@preprint\RESP@printlinecounttrue\fi

\RESP@linecount This is the box displayed in the manuscript mode
128 \ifRESP@printlinecount
129   \newsavebox{\RESP@linecount}
130   \savebox{\RESP@linecount}[4em][t]{\parbox[t]{4em}{%
131     \tempcnta\one\relax
132     \loop\color{red}\scriptsize\the\tempcnta\%
133     \advance\tempcnta by \one\ifnum\tempcnta<47\repeat}}
134 \fi

```

It is easy to set up headers with `fancyhdr`:

```

135 \pagestyle{fancy}
136 \fancyhead{}
137 \fancyfoot{}
138 \fancyhead[LE]{\footnotesize\thepage\quad\itshape\shortauthors}
139 \fancyhead[RO]{\footnotesize\textit{\shorttitle}\quad\thepage}
140 \ifRESP@printlinecount
141   \fancyhead[LE]{\begin{picture}(0,0)%
142     \put(-26,-22){\usebox{\RESP@linecount}}%
143   \end{picture}\footnotesize\thepage\quad\itshape\shortauthors}
144   \fancyhead[LO]{\begin{picture}(0,0)%
145     \put(-21,-22){\usebox{\RESP@linecount}}%
146   \end{picture}}
147 \fi
148 \ifRESP@manuscript
149   \fancyfoot[C]{\scriptsize\color{red}Author's Proof}%
150 \fi
151 \ifRESP@preprint
152   \fancyfoot[C]{\scriptsize\color{red}Author's Pre-Print}%
153 \fi

```

The first page has the special headers. The style `firstpage` is invoked by `amsart`; here we just redefine it.

```

154 \fancypagestyle{firstpage}{%
155   \fancyhf{}%
156   \ifRESP@printlinecount
157     \lhead{\begin{picture}(0,0)%
158       \put(-26,-20){\usebox{\RESP@linecount}}%
159     \end{picture}}
160   \fi
161 \ifRESP@preprint

```

```

162 \cfoot{\footnotesize Res Philosophica, \itshape
163   Vol.\~\currentvolume, No.\~\currentissue,
164   \currentmonth\~\currentyear
165   \ifx\@doinumber\@empty\else\\%
166   \doi{\@doinumber}\fi
167   \\
168   \@copyrightnote}%
169 \chead{\scriptsize\color{red}Author's Pre-print. Forthcoming in
170   Res Philosophica. Pagination may change. Published version will
171   be available at \url{http://pdcnet.org/resphilosophica/}}
172 \else
173 \ifRESP@forthcoming
174   \cfoot{\footnotesize Res
175     Philosophica\itshape
176     \ifx\currentvolume\@empty\else, %
177     Vol.\~\currentvolume\fi
178     \ifx\currentissue\@empty\else, No.\~\currentissue\fi
179     \ifx\currentmonth\@empty
180       \ifx\currentyear\@empty\else, \currentyear\fi
181     \else,
182       \currentmonth\~\currentyear
183     \fi
184     \ifx\@doinumber\@empty\else\\%
185     \doi{\@doinumber}\fi
186     \\
187   \@copyrightnote}%
188 \lhead{\raisebox{1.5\bigskipamount}{[\z@] [\z@]{\parbox{\textwidth}{\raggedright\footnotesize
189 \else
190   \cfoot{\footnotesize Res Philosophica, \itshape
191     \itshape Vol.\~\currentvolume, No.\~\currentissue,
192     \currentmonth\~\currentyear, pp.\~\start@page--\end@page
193     \ifx\@doinumber\@empty\else\\%
194     \doi{\@doinumber}\fi
195     \\
196   \@copyrightnote}%
197 \fi\fi}

```

4.5 Top Matter Macros

Most top matter macros are defined in `amsart`. Here we just add some new macros and redefine some.

The next macros mimic the functionality of `amsart \issueinfo` command. Note that `\issueinfo` still works.

- `\volumenumber` This sets the volume of the paper
198 `\def\volumenumber#1{\def\currentvolume{#1}}`
199 `\volumenumber{}`
- `\issuenumber` This sets the issue of the paper:

```

200 \def\issuenumber#1{\def\currentissue{#1}}
201 \issuenumber{}

\publicationyear This sets the year of the paper
202 \def\publicationyear#1{\def\currentyear{#1}}
203 \publicationyear{}

\publicationmonth This sets the month of the paper
204 \newcommand\publicationmonth[2][]{\gdef\currentmonth{#2}%
205   \gdef\abbrevcurrentmonth{#1}%
206   \ifx\abbrevcurrentmonth\empty\gdef\abbrevcurrentmonth{#2}\fi}
207 \publicationmonth{}

\papernumber This is absent from the \issueinfo.
208 \def\papernumber#1{\def\currentpaper{#1}}
209 \papernumber{0000}
210 %
211 % \end{macro}
212 %
213 %
214 % \begin{macro}{\doinumber}
215 % \changes{v1.11}{2012/12/25}{Added default}
216 % DOI number for the article:
217 % \begin{macrocode}
218 \def\doinumber#1{\gdef\@doinumber{#1}}
219 \doinumber{10.11612/resphil.\currentyear.\currentvolume.\currentissue.\currentpaper}

\paperUrl The url to submit to crossref
220 \def\paperUrl#1{\gdef\@paperUrl{#1}}
221 \paperUrl{}


\startpage This defines the starting page of the paper. We have some nice features to set up
roman page numbers for editorial stuff—probably not needed for this journal at
this time...
222 \def\startpage#1{\pagenumbering{arabic}\setcounter{page}{#1}%
223   \def\start@page{#1}%
224   \ifnum\c@page<\z@ \pagenumbering{roman}\setcounter{page}{-#1}%
225     \def\start@page{\romannumeral#1}%
226   \fi}

\endpage This macro again has a twist in it: if the argument is not set, it calculates the last
page number itself.
227 \def\endpage#1{\def\@tempa{#1}%
228   \ifx\@tempa\empty\def\end@page{\pageref{LastPage}}%
229   \else\def\end@page{#1}\fi}

\pagespan This macro is different from the one provided by amsart because we want to have
the option of automatic calculation of the last page number.
230 \def\pagespan#1#2{\startpage{#1}\endpage{#2}}
231 \pagespan{1}{}

```

\articleentry This is necessary for \prevpaper command. We read the TOC entry from the previous paper and increment it by 1. Note that we always start with on an odd page, since the additional check

```

232 \def\articleentry#1#2#3#4{\@tempcpta=#4\relax
233   \advance\@tempcpta by 1\relax
234   \ifodd\the\@tempcpta\else\advance\@tempcpta by 1\relax\fi
235   \startpage{\the\@tempcpta}}

```

\prevpaper This sets the previous paper location and reads the information from the previous paper

```

236 \def\prevpaper#1{\IfFileExists{#1.rpi}{%
237   \ClassInfo{resphilosophica}{%
238     Reading first page number from the file #1.rpi}%
239   \input{#1.rpi}%
240 }{\ClassWarning{resphilosophica}{Cannot find the file #1.rpi.%
241 Did you run latex on the previous paper?}}}

```

\abstract We slightly redefine abstract comparing to amsart conventions:

```

242 \renewenvironment{abstract}{%
243   \ifx\maketitle\relax
244     \ClassWarning{resphilosophica}{Abstract should precede
245       \protect\maketitle\space in AMS derived classes}%
246   \fi
247   \global\setbox\abstractbox=\vtop\bgroup%
248     \vglue1pc%
249     \list{}{\labelwidth\z@%
250       \leftmargin3pc \rightmargin\leftmargin%
251       \listparindent\normalparindent \itemindent\z@%
252       \parsep\z@ \z@plus\p@%
253       \let\fullwidthdisplay\relax%
254     }%
255     \item[]\normalfont\normalsize\textbf{\abstractname:}\space
256 }{%
257   \endlist\egroup%
258   \ifx\@setabstract\relax\@setabstract\fi%
259 }

```

\copyrightyear This is the copyright year in case it does not coincide with the publication year:

```

260 \def\copyrightyear#1{\def\@copyrightyear{#1}%
261 \ifRESP@forthcoming
262   \copyrightyear{\the\year}\else
263   \copyrightyear{}\fi

```

\onlinedate Online date for forthcoming issues

```

264 \def\onlinedate#1{\gdef\@onlinedate{#1}%
265 \onlinedate{\hspace*{5em}}}

```

\RESP@bulletboxwidth This is the width of a box with a bullet for copyright note:

```

266 \newlength\RESP@bulletboxwidth
267 \settowidth\RESP@bulletboxwidth{\quad\textbullet\quad}

```

`\copyrightnote` This is the `\copyrightnote`. The default has some trickery with the year and short authors.

The disappearing bullet is based on the trick by Marcin Wolinński, who noted that `\cleaders` are discardable (see [4]).

```
268 \def\copyrightnote{\def\@copyrightnote{#1}}
269 \copyrightnote{\textcopyright~%
270   \ifx\@empty\@copyrightyear\currentyear\else\@copyrightyear\fi~%
271   \shortauthors\cleaders\hbox{\quad\textbullet\quad}\hskip\RESP@bulletboxwidth
272   \textcopyright~%
273   \ifx\@empty\@copyrightyear\currentyear\else\@copyrightyear\fi~%
274   {\upshape Res~Philosophica}}%
```

`\author` The base class puts into `\addresses` the strange line `\author{}`. We correct this:

```
275 \renewcommand{\author}[2][]{%
276   \ifx\@empty\addresses
277     \gdef\addresses{\author{#2}}%
278   \else
279     \g@addto@macro\addresses{\author{#2}}%
280   \fi
281   \ifx\@empty\authors
282     \gdef\authors{\#2}%
283   \else
284     \g@addto@macro\authors{\and#2}%
285   \fi
286   \@ifnotempty{#1}{%
287     \ifx\@empty\shortauthors
288       \gdef\shortauthors{\#1}%
289     \else
290       \g@addto@macro\shortauthors{\and#1}%
291     \fi
292   }%
293 }
294 \edef\author{\@nx\@dblarg
295   \exp\@nx\csname\string\author\endcsname}
```

`\titlenote` This command adds an entry to the list of titlenotes

```
296 \def\@titlenotes{}%
297 \def\titlenote#1{%
298   \ifx\@empty\@titlenotes\gdef\@titlenotes{\footnote{#1}}%
299   \else\g@addto@macro\@titlenotes{\footnote{#1}}\fi}
```

`\authornote` This command adds an entry to the list of titlenotes

```
300 \def\@authornotes{}%
301 \def\authornote#1{%
302   \ifx\@empty\@authornotes\gdef\@authornotes{\footnote{#1}}%
303   \else\g@addto@macro\@authornotes{\footnote{#1}}\fi}
```

4.6 Typesetting Top Matter

\@settitle We do not uppercase title. Also, we use this occasion to set PDF information:

```
304 \def\@settitle{\begin{center}%
305   \baselineskip20\p@\relax
306   \LARGE\scshape
307   \renewcommand\thefootnote{\@fnsymbol\c@footnote}%
308   \ifx\itscshape\@undefined\else\def\em{\it\itscshape}\fi
309   \@title\@titlenotes
310   \hypersetup{pdftitle=\@title}%
311   \end{center}%
312 }
```

\@setauthors Now we typeset authors according to our specs. Again, we use this occasion to set some PDF information:

```
313 \def\@setauthors{%
314   \ifx\authors\@empty\relax\else
315     \begingroup
316     \def\thanks{\protect\thanks@warning}%
317     \trivlist
318     \centering\footnotesize \topsep30\p@\relax
319     \advance\topsep by -\baselineskip
320     \item\relax
321     \def\@@and{{and}}
322     \author@andify\authors
323     \hypersetup{pdfauthor=\authors}%
324     \def\\{\protect\linebreak}%
325     \renewcommand\thefootnote{\@fnsymbol\c@footnote}%
326     \large\normalfont\authors\@authornotes
327     \endtrivlist
328     \endgroup
329   \fi}
```

\maketitle We redefine \maketitle—mostly to prevent uppercasing of shorttitle and to write down the journal iformation:

```
330 \def\maketitle{\par
331   \topnum\z@ % this prevents figures from falling at the top of page 1
332   \setcopyright
333   \thispagestyle{firstpage} % this sets first page specifications
334   \ifx\@empty\shortauthors \let\shortauthors\shorttitle
335   \else \andify\shortauthors
336   \fi
337   \maketitle@hook
338   \RESP@write@paper@info
339   \begingroup
340   \maketitle
341   \toks@{\exp{\shortauthors}\@temptokena\exp{\shorttitle}}%
342   \toks4{\def\\{\ignorespaces}}% defend against questionable usage
343   \edef\@tempa{%
```

```

344     \@nx\markboth{\the\toks4
345         \@nx\MakeUppercase{\the\toks@}{\the\@temptokena}}%
346     \@tempa
347     \endgroup
348     \c@footnote{z@}
349     \everypar{\setbox\z@\lastbox\everypar{}}
350 }

```

\@maketitle We delete top space introduced by amsart:

```

351 \def\@maketitle{%
352   \normalfont\normalsize
353   \@adminfootnotes
354   \@mkboth{\@nx\shortauthors}{\@nx\shorttitle}%
355   \settowidth
356   \ifx\@empty\authors \else \setauthor \fi
357   \ifx\@empty\@dedicatory
358   \else
359     \baselineskip18\p@
360     \vtop{\centering{\footnotesize\itshape\@dedicatory\@@par}%
361       \global\dimen@i\prevdepth}\prevdepth\dimen@i
362   \fi
363   \setabstract
364   \normalsize
365   \iftitlepage
366     \newpage
367   \else
368     \dimen@34\p@ \advance\dimen@-\baselineskip
369     \vskip\dimen@\relax
370   \fi
371 } % end \@maketitle

```

\@mainrpi The stream for the rpi file:

```
372 \newwrite\@mainrpi
```

\RESP@write@paper@info This writes the information about the paper into the file `jobname.rpi`. Note that hyperref makes our life a little bit more complex

```

373 \def\RESP@write@paper@info{%
374   \bgroup
375   \if@filesw
376     \openout\@mainrpi\jobname.rpi%
377     \write\@mainrpi{\relax}%
378     \ifx\r@LastPage\undefined
379       \edef\@tempa{\start@page}%
380     \else
381       \def\@tempc##1##2##3##4##5{##2}%
382       \edef\@tempa{\expandafter\@tempc\r@LastPage}%
383     \fi
384     \def\and{\string\and\space}%
385     \protected@write\@mainrpi{}{%
386       \string\articleentry{\authors}{\@title}{\start@page}{\@tempa}}%

```

The next lines are for crossref software

```
387 \protected@write\@mainrpi{}%
388 {\@percentchar authors=\authors}%
389 \protected@write\@mainrpi{}%
390 {\@percentchar title=\@title}%
391 \protected@write\@mainrpi{}%
392 {\@percentchar year=\currentyear}%
393 \protected@write\@mainrpi{}%
394 {\@percentchar volume=\currentvolume}%
395 \protected@write\@mainrpi{}%
396 {\@percentchar issue=\currentissue}%
397 \protected@write\@mainrpi{}%
398 {\@percentchar paper=\currentpaper}%
399 \protected@write\@mainrpi{}%
400 {\@percentchar startpage=\start@page}%
401 \protected@write\@mainrpi{}%
402 {\@percentchar endpage=\@tempa}%
403 \protected@write\@mainrpi{}%
404 {\@percentchar doi=\@doinumber}%
405 \ifx\@paperUrl\@empty\else
406 \protected@write\@mainrpi{}%
407 {\@percentchar paperUrl=\@paperUrl}%
408 \fi
409 \closeout\@mainrpi
410 \fi
411 \egroup}
```

\@adminfootnotes We just define this to noop:

```
412 \def\@adminfootnotes{}
```

\@cleartopmattertags We typeset thankses at the end of the paper so we do not clear them:

```
413 \def\@cleartopmattertags{%
414 \def\do##1{\let##1\relax}%
415 \do\maketitle \do\@maketitle \do\title \do\xtitle \do\@title
416 \do\author \do\@xauthor \do\address \do\@xaddress
417 \do\contrib \do\@contribs \do\xcontribs \do\@toccontribs
418 \do@email \do\@xemail \do\curraddr \do\@curraddr
419 \do\commby \do\@commby
420 \do\dedicatory \do\@dedicatory \do\thanks
421 \do\keywords \do\@keywords \do\subjclass \do\@subjclass}
```

\sf@size It seems there is a bug in mdugm when calculating \sf@size. Here we work around it:

```
422 \def\sf@size{7}%

423 }
```

4.7 Notes

```
\notes This is like bibliography:  
424 \definecollection{notes}  
425 \newenvironment{notes}[1]{%  
426   \nameuse{collect}{notes}{}{}%  
427   \makeatletter  
428   \par\addpenalty\@secpenalty\addvspace{\bigskipamount}%  
429   \noindent \Small #1:\par\nobreak\vskip\medskipamount\@afterheading  
430   \makeatother  
431 }{\nameuse{endcollect}\AddtoEndMatter{\includecollection{notes}}}
```

4.8 Typesetting End Matter

End matter is typeset at the end of the paper.

`\if@enddoc` Check whether we are in the end matter

```
432 \newif\if@enddoc  
433 \ifenddocfalse
```

`\enddoc@text` We put thankses into end matter. Also, we redefine bibliography back to the original definition in case someone writes `\AddtoEndMatter{\bibliography{}}`

```
434 \def\enddoc@text{  
435   \ifenddoctrue\def\bibliography{\RESP\bibliography}%  
436   \ifx\empty\thankses\else  
437   \bgroup  
438   \let\makefnmark\relax  
439   \let\thefnmark\relax
```

Check, whether we are at the same page as the last footnote; if yes, add medskip.

```
440   \ifx\lastfootnote@page\undefined\else  
441     \tempcnta=\lastfootnote@page\relax  
442     \ifnum\c@page=\tempcnta\relax  
443       \insert\footins{\medskip}%  
444     \fi  
445   \fi  
  
446   \footnotetext{  
447     \def\par{\let\par\@par}\textbf{Acknowledgements}\quad} \setthanks{  
448   \egroup  
449   \fi  
450   \ifx\empty@translators \else\settranslators\fi  
451   \ifx\empty@addresses \else\setaddresses\fi}
```

`\ifRESP@firstingroup` A group of authors is separated by a skip from another group. This macro checks whether this is the first one

```
452 \newif\ifRESP@firstingroup
```

`\emailaddrname` The name for e-mail address:

```
453 \def\emailaddrname{E-mail}
```

\@setaddresses Unlike `aomart`, we want to preserve author's name in the address block. Also, we want to keep linebreaks and to have clickable e-mail and URL.

We want to skip between the author groups (several authors with the same affiliation), so we check whether the previous line contains another author:

```

454 \def\@setaddresses{\par
455   \nobreak \begingroup\flushright\clubpenalty\OMM\interlinepenalty\OMM
456   \widowpenalty\OMM
457   \RESP@firstingrouptrue
458   \Small
459   \def\author##1{\nobreak\ifRESP@firstingroup\par
460     \addvspace\bigskipamount\penalty-1000\fi
461     \RESP@firstingroupfalse##1\par\nobreak}%
462   \parindent\z@
463   \def\address##1##2{\RESP@firstingrouptrue\begingroup
464     \par\nobreak
465     \ifnotempty{##1}{(\ignorespaces##1\unskip) }%
466     {(\ignorespaces##2)\par\endgroup}%
467   \def\curraddr##1##2{\RESP@firstingrouptrue\begingroup
468     \ifnotempty{##2}{\nobreak\indent\curraddrname
469       \ifnotempty{##1}{, \ignorespaces##1\unskip}\hspace{0.2em}:\space
470       ##2\par}\endgroup}%
471   \def\email##1##2{\RESP@firstingrouptrue\begingroup
472     \ifnotempty{##2}{\nobreak\indent\emailaddrname
473       \ifnotempty{##1}{, \ignorespaces##1\unskip}\hspace{0.2em}:\space
474       \href{mailto:##2}{\nolinkurl{##2}}\par}\endgroup}%
475   \def\urladdr##1##2{\RESP@firstingrouptrue\begingroup
476     \ifnotempty{##2}{\nobreak\indent
477       \ifnotempty{##1}{, \ignorespaces##1\unskip}%
478       \url{##2}\par}\endgroup}%
479   \addresses
480   \endgroup
481 }

```

At the end we eject the last page. If the document is printed and the last page is odd, we add an empty page.

```

482 \AtEndDocument{\clearpage
483   \ifRESP@manuscript\else
484   \ifRESP@screen\else
485   \ifRESP@preprint\else
486   \ifRESP@forthcoming\else
487   \cleardoublepage
488   \fi\fi\fi\fi}

```

4.9 Sectioning

\@secntformat We do not want our numbers to be upright and medium series, as `amsart` wants:

```

489 \def\@secntformat#1{%
490   \csname the#1\endcsname\enspace
491 }

```

```

\section We want our sections to be large and bold:
492 \renewcommand\section{\@startsection {section}{1}{\z@}%
493                                     {-3.5ex \oplus -1ex \ominus -.2ex}%
494                                     {2.3ex \oplus .2ex}%
495                                     {\normalfont\large\bfseries}%

\subsection Subsections are bold
496 \renewcommand\subsection{\@startsection{subsection}{2}{\z@}%
497                                     {-3.25ex \oplus -1ex \ominus -.2ex}%
498                                     {1.5ex \oplus .2ex}%
499                                     {\normalfont\normalsize\bfseries}%

\subsubsection Subsubsections are normalsize and italic
500 \renewcommand\subsubsection{\@startsection{subsubsection}{3}{\z@}%
501                                     {-3.25ex \oplus -1ex \ominus -.2ex}%
502                                     {1.5ex \oplus .2ex}%
503                                     {\normalfont\normalsize\itshape}%

\paragraph Paragraphs:
504 \renewcommand\paragraph{\@startsection{paragraph}{4}{\z@}%
505                                     {3.25ex \oplus 1ex \ominus .2ex}%
506                                     {-1em}%
507                                     {\normalfont\normalsize\bfseries}%

\ subparagraph Paragraphs:
508 \renewcommand\subparagraph{\@startsection{subparagraph}{5}{\parindent}%
509                                     {3.25ex \oplus 1ex \ominus .2ex}%
510                                     {-1em}%
511                                     {\normalfont\normalsize\bfseries}}%

```

4.10 Additional Commands

```

\@mparswitch We always put marginpars on the right since the line box is on the left
512 \@mparswitchfalse

\EditorialComment This macro is noop in normal mode, but is a tiny marginpar in the manuscript
mode
513 \newcommand\EditorialComment[2][0]{%
514   \expandafter\ifx\csname EditorialComment@\#1\endcsname\relax
515   \else\bgroup
516   \marginparwidth=200pt\marginpar{\color{red}%
517     \raggedright#2}\egroup\fi}

\ECSelect This selects the given levels
518 \def\ECSelect#1{\ifRESP@manuscript
519   \@for\EC@level:=#1\do{%
520     \expandafter\gdef\csname
521       EditorialComment@\EC@level\endcsname{\EditorialComment}%
522   \fi}

```

\TC The command to highlight text if the corresponding level is selected. The first argument is the level, the second is text.

```
523 \newcommand\TC[2][0]{%
524   \expandafter\ifx\csname TC@highlight@\#1\endcsname\relax#2\else
525   \csname TC@highlight@\#1\endcsname{\#2}\fi}
```

\TCSelect This switches on the selected levels in the mqnuscript version

```
526 \newcommand\TCSelect[2][magenta]{\ifRESP@manuscript
527   \@for\TC@level:=#2\do{\expandafter
528     \gdef\csname TC@highlight@\TC@level\endcsname##1{\bgroup
529       \Hy@colorlinksfalse
530       \def\Hy@colorlink####1{\begingroup}%
531       \def\Hy@endcolorlink{\endgroup}%
532       \color{#1}##1\egroup}%
533   \fi}
```

\doi Typesetting doi...

```
534 \def\doi#1{\url{http://dx.doi.org/#1}}
```

\@makefnmark The definition of \@makefnmark in amsart has a bug. Here we return to the L^AT_EX one:

```
535 \def\@makefnmark{\hbox{\@textsuperscript{\normalfont\@thefnmark}}}
```

\@makefntext Unlike amsart, we do not indent footnotes:

```
536 \def\@makefntext{\noindent\@makefnmark
537   \if@enddoc\else
538     \immediate\write\@mainaux{%
539       {\string\xdef\string\lastfootnote@page{\the\c@page}}%
540     \fi}
541 \long\def\@footnotetext#1{%
542   \insert\footins{%
543     \normalfont\footnotesize
544     \interlinepenalty\interfootnotelinepenalty
545     \splittopskip\footnotesep \splitmaxdepth \dp\strutbox
546     \floatingpenalty\@MM \hsize\columnwidth
547     \parboxrestore \parindent\normalparindent \sloppy
548     \protected@edef\@currentlabel{%
549       \csname p@footnote\endcsname\@thefnmark}%
550     \@makefntext{%
551       \rule{z@footnotesep}{\ignorespaces#1\unskip\strut\par}}}}
```

4.11 The End

Philosophers love footnotes, since \raggedbottom

```
552 \raggedbottom\normalsize\normalfont
553 </class>
```

References

- [1] Boris Veytsman. *Support files for the Linotype Sabon Fonts*, August 2015. <http://mirrors.ctan.org/fonts/lsabon/>.
- [2] Patrick W. Daly. *Natural Sciences Citations and References (Author-Year and Numerical Schemes)*, February 2009. <http://mirrors.ctan.org/macros/latex/contrib/natbib>.
- [3] American Mathematical Society. *Instructions for Preparation of Papers and Monographs, AMS \TeX* , August 2004. <http://mirrors.ctan.org/macros/latex/required/amslatex/classes/instr-1.pdf>.
- [4] Paweł Jackowski. \TeX beauties and oddities. *TUGboat*, 29:207–215, 2008. <http://www.tug.org/TUGboat/tb29-1/tb91pearls.pdf>.

Change History

v1.1	\@maketitle: Redefined macro	19	\publicationyear: The default is now empty	15
	\@mparswitch: Changed default	23	\RESP@printlinecount: Added macro	13
	\@setauthors: Changed font	18	\titlenote: Added command	17
	General: Added DOI number	1	\volumenumber: The default is now empty	14
	Added MT Shadow Imprint code	1		
	\doi: Added macro	24	v1.14	
	\EditorialComment: Added macro	23	\sf@size: Bug corrected	20
	\ifRESP@mtshadow: Added macro	9		
	\ifRESP@rpfonauto: Added macro	9	v1.15	
	\rpfont: Added option	9	General: Added new bibliography command	1
	\RESP@write@paper@info: Added protection for \\	19		
	\rpdefault: Added macro	11	v1.16	
	\section: Moved to LaTeX defaults	23	\@makefntext: Added small space after footnote mark	24
	\subsection: Moved to LaTeX defaults	23	\@onlinedate: Added macro	16
	\subsubsection: Moved to LaTeX defaults	23	General: Added \bfdefault	11
v1.10	General: Bibliography changes	1	Added documentation about typesetter changes highlighting	1
v1.11	General: Bibliography changes	1	Deleted Imprint Shadow	1
	\papernumber: Added macro	15	\copyrightnote: Deleted rpdefault	17
	\RESP@write@paper@info: Added writing info for crossref	19	\ifRESP@mtshadow: Deleted macro	9
v1.12	General: Bibliography changes	1	\maketitle: Added suppressing first para indentation	18
v1.13	\@setttitle: Added titlenotes	18	\notes: Added macro	21
	General: Changed check for line numbering mode	13	\onlinedate: Added macro	16
	New command: titlenote	1	\rpfont: Deleted option	9
	New options: preprint and forthcoming	1	\publicationmonth: Added \abrevcurrentmonth	15
	\copyrightnote: Changed font family for forthcoming mode	17	\rpdefault: Deleted macro	11
	\ifRESP@forthcoming: Added option	10	\TC: Added macro	24
	\ifRESP@preprint: Added option	10	\TCSelect: Added macro	24
	\issuenumber: The default is now empty	14		
	\publicationmonth: The default is now empty	15	v1.17	
			General: Added collect package	11
			Added documentation about new editorial comments	1
			Bibliography changes: ‘inloosecollection’ entry	1
			Journal name on the first page footer is now italic	13
			Online date for forthcoming option moved to the left and up	13
			\ECSelect: Added macro	23
			\EditorialComment: Redefined so levels are supported	23

\notes:	Redefined using collect package	21	General:	New command: authornote	1	
v1.18	General: Journal name in Roman	13	\authornote:	Added command	17	
	Online date for forthcoming option moved down	13	v1.25	\oddsidemargin:	Changed margins	12
	\copyrightnote:	Made journal name Roman	\pdfpaperheight:	Returned to old page width	12	
v1.19	\TCSelect:	Switched off colored links	v1.26	\@settitle:	Added itscshape	18
v1.2	\@adminfootnotes:	Redefined	v1.27	General:	New command: ensquote	1
	\@cleartopmattertags:	Redefined	v1.28	General:	Now ensquote and enquote work correct in the case of embedded quotations	1
	\@setaddresses:	Changed font	v1.3	\@setaddresses:	Added penalties	22
	\@setauthors:	Changed font	\@setauthors:	Deleted ifpdf	18	
	General:	Changed font for bibliography	\@settitle:	Deleted ifpdf	18	
		Changed skip for bibliography	General:	Added penalties	11	
	\copyrightnote:	Used \rpdefault for RP font	Ifpdf is no longer needed with modern engines		11	
	\enddoc@text:	Redefined	\copyrightyear:	In the forthcoming mode the copyright year is the present year	16	
	\listisep:	Redefined	\pdfpaperheight:	Deleted ifpdf	12	
	\RESP@write@paper@info:	Used \protected@write	\RESP@linecount:	Changed check for linecount	13	
	\section:	Changed font	v1.4	\@makefnmark:	Redefined	24
	\subsection:	Changed font	General:	Added footmisc package with 'bottom' option	11	
	\subsubsection:	Changed font		Added screen option	1	
v1.20	\@makefnmark:	Redefined		Changed bibsection font	11	
v1.21	\paperUrl:	Added macro		Changed color of "Author's proof" mark	13	
	\RESP@write@paper@info:	Added paperUrl	\EditorialComment:	Changed color	23	
v1.22	General:	Now we add empty even page at the end for printed version only		Changed font	23	
v1.23	General:	Switched to twoside mode of amsart	\ifRESP@screen:	Added option	10	
	\oddsidemargin:	Made even- and odd- side margins different, except in screen and forthcoming modes	\paragraph:	Moved to LaTeX default	23	
	\pdfpaperheight:	Added to paper width to accomodate larger thumb side margins	\pdfpaperheight:	Changed paper in the manuscript mode	12	
v1.24	\@setauthors:	Added authornotes	\RESP@linecount:	Changed color	13	
		18	\ subparagraph:	Moved to LaTeX default	23	

v1.5	
\@makefntext:	Added writing the current footnote page to the aux file
General:	Changed color for headers and footers
Color change for links	
Hyperfootnotes are incompatible with hyperref	
\EditorialComment:	Changed color
\enddoc@text:	Added flag
\if@enddoc:	Added macro
\RESP@linecount:	Changed color
v1.6	General: Changed bib style
v1.7	General: Added new bibliography
	fields
	Changed formatting of doi
\doi:	Changed formatting
\footskip:	Decreased to fit doi number
v1.8	General: Added blank last page if the last page is odd
\enddoc@text:	Changed bibliography
\sf@size:	Added definition
v1.9	\@setaddresses: Added penalties
\copyrightnote:	Made bullet disappear at break
\RESP@bulletboxwidth:	Added macro

Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	
\,	551
\@and	321
\@par	360
\@MM	455, 456, 546
\@adminfootnotes	353, <u>412</u>
\@afterheading	98, 429
\@authornotes	300, 302, 303, 326
\@cleartopmattertags	413
\@commby	419
\@copyrightnote	168, 187, 196, 268
\@copyrightyear	260, 270, 273
\@currentlabel	548
\@dbllarg	294
\@dedicatory	357, 360, 420
\@doinumber	165, 166, 184, 185, 193, 194, 218, 404
\@empty	165, 176, 178, 179, 180, 184, 193, 206, 228, 270, 273, 276, 281, 287, 298, 302, 314, 334, 356, 357, 405, 436, 450, 451
\@enddocfalse	433
\@enddoctype	435
\@fnsymbol	307, 325
\@footnotetext	446, 541
\@for	519, 527
\@ifnotempty	286, 465, 468, 469, 472, 473, 476, 477
\@keywords	421
\@mainaux	538
\@mainrpi	<u>372</u> , 376, 377, 385, 387, 389, 391, 393, 395, 397, 399, 401, 403, 406, 409
\@makefnmark	438, <u>535</u> , 536
\@makefntext	<u>536</u>
\@maketitle	340, <u>351</u> , 415
\@maketitle@hook	337
\@minus	493, 497, 501, 505, 509
\@mkboth	354
\@mparswitch	<u>512</u>
\@mparswitchfalse	512
\@nameuse	426, 431
\@ne	131, 133
\@nx	294, 295, 344, 345, 354
\@onlinedate	188, <u>264</u>
\@paperUrl	220, 405, 407
\@par	447
\@parboxrestore	<u>547</u>
\@percentchar 388, 390, 392, 394, 396, 398, 400, 402, 404, 407
\@plus	252, 493, 494, 497, 498, 501, 502, 505, 509
\@secCntformat	<u>489</u>
\@secPenalty	97, 428
\@setAbstract	258, 363
\@setAbtracta	258
\@setAddresses	451, <u>454</u>
\@setAuthors	<u>313</u> , 356
\@setCopyright	332
\@setThanks	447
\@setTitle	<u>304</u> , 355
\@setTranslators	450
\@startSection	492, 496, 500, 504, 508
\@subjClass	421
\@tempa	227, 228, 343, 346, 379, 382, 386, 402
\@tempc	381, 382
\@tempcnta	131, 132, 133, 232, 233, 234, 235, 441, 442
\@temptokena	341, 345
\@textsuperscript	535
\@thefnmark	439, 535, 549
\@title	309, 310, 386, 390, 415
\@titlenotes 296, 298, 299, 309
\@topnum	331
\@topsep	318, 319
\@translators	450
\@undefined	308, 378, 440
\@xaddress	416
\@xauthor	416
\@xcurraddr	418
\@xemail	418
\@xp	295, 341
\@xtitle	415
\\"	132, 165, 167, 184, 186, 193, 195, 324, 342
A	
\abbrevCurrentMonth	205, 206
\abstract	<u>242</u>
abstract (environment)	4
\abstractbox	247
\abstractName	255
\addPenalty	97, 428
\address	3, 416, 463
\addresses	276, 277, 279, 451, 479
\AddToEndMatter	8, <u>91</u> , 96, 431
\addvspace	97, 428, 460

\advance	133,	\clubpenalty	455	447, 453, 454,
233, 234, 319, 368		\color	132, 149,	459, 463, 467,
\and	284, 290, 384	152, 169, 516, 532		471, 475, 489,
\andify	335	\columnwidth	546	518, 530, 531,
\articleentry . <u>232</u> , 386		\commby	419	534, 535, 536, 541
\AtBeginDocument . . 102		\contrib	417	\define@boolkey . . . 42
\AtEndDocument . . 94, 482		\contribs	417	\define@choicekey 10, 26
\author . <u>3</u> , <u>275</u> , 416, 459		\copyrightnote . . . 4, <u>268</u>		\definecollection . 424
\author@andify	322	\copyrightyear . . . 4, <u>260</u>		\dimen@ 368, 369
\authornote	<u>4</u> , <u>300</u>	\csname	295,	\dimen@i 361
\authors	281, 282, 284,	490, 514, 520,		\do 414, 415, 416,
314, 322, 323,		524, 525, 528, 549	417, 418, 419,	
326, 356, 386, 388		\curraddr	420, 421, 519, 527	
B		\curraddrname		
\baselineskip 305, 319, 359, 368	\currentissue		\doi 166, 185, 194, <u>534</u>
\begin	141, 144,	. 163, 178,		\doinumber
157, 214, 217, 304		191, 200, 219, 396	5, 214, 218, 219	
\begingroup	315,	\currentmonth	545	
339, 455, 463,		164,		
467, 471, 475, 530		179, 182, 192, 204		
\bfdefault	84	\CurrentOption	49,	E
\bfseries 495, 499, 507, 511	50, 51, 52, 53, 66	\EC@level 519, 521	
\bgroup	247,	\currentpaper	\ECSelect 6, <u>518</u>	
374, 437, 515, 528		. 208, 219, 398	\edef 294, 343, 379, 382	
\bibfont	99	\currentvolume	\EditorialComment 5, <u>513</u> , 521	
\bibliography	95, 96, 435	. 163, 176, 177,	\egroup 257,	
\bibliographystyle	94	191, 198, 219, 394	411, 448, 517, 532	
\bibsection	97	\currentyear	\else 73, 74, 75,	
\bigskipamount 97, 188, 428, 460	164, 180,	76, 89, 101, 165,	
\bodyfont	<u>10</u>	182, 192, 202,	172, 176, 178,	
bodyfont (option)	<u>2</u>	219, 270, 273, 392	180, 181, 184,	
C			189, 193, 229,	
\c@footnote	307, 325, 348	\DeclareOptionX	234, 262, 270,	
\c@page	224, 442, 539	49,	273, 278, 283,	
\centering	318, 360	50, 51, 52, 53,	289, 299, 303,	
\cfoot	162, 174, 190	56, 59, 62, 65, 66	308, 314, 335,	
\changes	215	\dedicatory	356, 358, 367,	
\chead	169	420	380, 405, 436,	
\ClassInfo	237	\def	440, 450, 451,	
\ClassWarning 47, 240, 244	46, 89, 90, 91,	483, 484, 485,	
\cleaders	271	96, 97, 99, 198,	486, 515, 524, 537	
\cleardoublepage	487	200, 202, 208,	\em 308	
\clearpage	482	218, 220, 222,	\email 3, 418, 471	
\closeout	409	223, 225, 227,	\emailaddrname 453, 472	
		228, 229, 230,	\end 143,	
		232, 236, 260,	146, 159, 211, 311	
		264, 268, 296,	\end@page 192, 228, 229	
		297, 300, 301,	\endcsname 295,	
		304, 308, 313,	490, 514, 521,	
		316, 321, 324,	524, 525, 528, 549	
		330, 342, 351,	\enddoc@text 91, <u>434</u>	

<pre> \endgroup 328, 162, 174, 188, \ifRESP@mtshadow . 8, 88 347, 466, 470, 190, 318, 360, 543 \ifRESP@natbib 92 474, 478, 480, 531 \footrulewidth 121 \ifRESP@preprint \endlist 257 \footskip 123 60, 75, \endpage 5, 227, 230 forthcoming (option) . 3 127, 151, 161, 485 \endtrivlist 327 \fullwidthdisplay . 253 \ifRESP@printlinecount \enquote 7 \g@addto@macro 124, 128, 140, 156 \enspace 490 \G \ifRESP@rpfontauto 4, 86 \ensquote 7 environments: \gdef 165, 176, 178, abstract 4 284, 290, 299, 303 179, 180, 184, notes 6 \gdef 204, 205, 206, 193, 206, 228, \evensidemargin 107 218, 220, 264, 243, 258, 270, \everypar 349 277, 282, 288, 273, 276, 281, \expandafter 382, 298, 302, 520, 528 287, 298, 302, 514, 520, 524, 527 \global 247, 361 308, 314, 334, \fi \F \H 356, 357, 378, \fancyfoot 137, 149, 152 \hbox 271, 535 405, 436, 440, \fancyhead 136, \headheight 120 450, 451, 514, 524 138, 139, 141, 144 \headrulewidth 121 \ignorespaces \fancyhf 155 \headsep 119 342, 465, 466, \fancypagestyle 154 \href 474 469, 473, 477, 551 \fi 23, 39, 77, 79, 85, \hsize 546 \immediate 538 87, 90, 100, 104, \hskip 271, 469, 473 \includecollection . 431 112, 116, 126, \hspace 265 \indent 468, 472, 476 127, 134, 147, \Hy@colorlink 530 \input 239 150, 153, 160, \Hy@colorlinksfalse 529 \insert 443, 542 166, 177, 178, \Hy@endcolorlink 531 \interfootnotelinepenalty 180, 183, 185, \hypersetup 73, 74, 544 194, 197, 206, 75, 76, 77, 310, 323 \interlinepenalty 226, 229, 234, 455, 544 246, 258, 263, \issuenumber 5, 200 270, 273, 280, \item 255, 320 285, 291, 299, \itemindent 251 303, 308, 329, \itscshape 308 336, 356, 362, \itshape 138, 370, 383, 408, 143, 162, 175, 410, 444, 445, \ifnum 133, 224, 442 190, 191, 360, 503 449, 450, 451, \ifodd 234 460, 488, 517, \ifRESP@firstingroup \J 522, 525, 533, 540 452, 459 \jobname 376 \floatingpenalty 546 \ifRESP@fontauto . 2, 78 \flushright 455 \ifRESP@forthcoming \K \footins 443, 542 63, 76, \footnote 298, 299, 302, 303 113, 173, 261, 486 \footnotesep 545, 551 \ifRESP@lsabon 6, 80 \keywords 421 \footnotesize 138, 139, 143, \ifRESP@manuscript 54, 73, 101, 126, \labelwidth 249 148, 483, 518, 526 \LARGE 306 148, 483, 518, 526 \large 326, 495 </pre>	<pre> \ifRESP@mtshadow . 8, 88 \ifRESP@natbib 92 \ifRESP@preprint \ifRESP@printlinecount . 124, 128, 140, 156 \ifRESP@rpfontauto 4, 86 \ifRESP@screen \ifx 165, 176, 178, 179, 180, 184, 193, 206, 228, 243, 258, 270, 273, 276, 281, 287, 298, 302, 308, 314, 334, 356, 357, 378, 405, 436, 440, 450, 451, 514, 524 \ignorespaces 342, 465, 466, 469, 473, 477, 551 \immediate 538 \includecollection . 431 \indent 468, 472, 476 \input 239 \insert 443, 542 \interfootnotelinepenalty 544 \interlinepenalty 455, 544 \issuenumber 5, 200 \item 255, 320 \itemindent 251 \itscshape 308 \itshape 138, 143, 162, 175, 190, 191, 360, 503 \ifnum 133, 224, 442 \ifodd 234 \ifRESP@firstingroup \J 452, 459 \jobname 376 \ifRESP@fontauto . 2, 78 \ifRESP@forthcoming \K \ifRESP@lsabon 6, 80 \keywords 421 \ifRESP@manuscript \labelwidth 249 \LARGE 306 \large 326, 495 </pre>
---	---

```

\lastbox ..... 349 \normalparindent ... \ProcessOptionsX ... 67
\lastfootnote@page ..... 251, 547
    .... 440, 441, 539 \normalsize ... 255,
\leftmargin ..... 250 352, 364, 499,
\let ... 95, 253, 334, 503, 507, 511, 552
    414, 438, 439, 447 \notes ..... 424
\lhead ..... 157, 188 notes (environment) ... 6
\linebreak ..... 324 \nr ..... 10, 12, 26, 28
\list ..... 249
\listsep ..... 118
\listparindent ..... 251 \oddsidemargin ... 107
\LoadClass ..... 68 \onlinedate ..... 3, 264
\long ..... 46, 541 \openout ..... 376
\loop ..... 132 options:
    bodyfont ..... 2
    M forthcoming ..... 3
\makeatletter ..... 427 manuscript ..... 3
\makeatother ..... 430 natbib ..... 3
\maketitle ..... 4, preprint ..... 3
    243, 245, 330, 415 screen ..... 3
\MakeUppercase ..... 345 \or 14, 17, 20, 30, 33, 36
\manuscript (option) ... 3
\marginpar ..... 516
\marginparwidth ... 516
\markboth ..... 344
\medskip ..... 443
\medskipamount .....
    .... 98, 118, 429
\N
\natbib ..... 42
\natbib (option) ... 3
\newcommand .....
    . 204, 513, 523, 526
\newenvironment ... 425
\newif 2, 4, 6, 8, 54, 57,
    60, 63, 124, 432, 452
\newlength ..... 266
\newpage ..... 366
\newsavebox ..... 129
\newwrite ..... 372
\nobreak ... 98, 429,
    455, 459, 461,
    464, 468, 472, 476
\noindent . 98, 429, 536
\nolinkurl ..... 474
\normalfont ... 255,
    326, 352, 495,
    499, 503, 507,
    511, 535, 543, 552
\normalparindent ... 251, 547
\ normalsize ... 255,
\leftmargin ..... 250 352, 364, 499,
\let ... 95, 253, 334, 503, 507, 511, 552
\notes ..... 424
notes (environment) ... 6
\nr ..... 10, 12, 26, 28
\oddsidemargin ... 107
\onlinedate ..... 3, 264
\openout ..... 376
options:
    bodyfont ..... 2
    forthcoming ..... 3
    manuscript ..... 3
    natbib ..... 3
    preprint ..... 3
    screen ..... 3
\or 14, 17, 20, 30, 33, 36
\PackageWarning ...
    .... 24, 40, 43
\pagenumbering 222, 224
\pageref ..... 228
\pagespan ..... 230
\pagestyle ..... 135
\papernumber ... 5, 208
\paperUrl ..... 5, 220
\par ..... 97, 98,
    330, 428, 429,
    447, 454, 459,
    461, 464, 466,
    470, 474, 478, 551
\paragraph ..... 504
\parbox ..... 130, 188
\parindent 462, 508, 547
\parsep ..... 252
\PassOptionsToClass 66
\pdfpageheight ... 103
\pdfpagewidth ... 102
\pdfpaperheight ... 101
\pdfpaperwidth ... 101
\penalty ..... 460
\preprint (option) ... 3
\prevdepth ..... 361
\prevpaper ..... 5, 236
\ProcessOptionsX ... 67
\protect .. 245, 316, 324
\protected@edef ... 548
\protected@write 385,
    387, 389, 391,
    393, 395, 397,
    399, 401, 403, 406
\publicationmonth 5, 204
\publicationyear 5, 202
\put ..... 142, 145, 158
\Q
\qquad ..... 138, 139, 143
\quad ..... 267, 271, 447
\R
\r@LastPage ... 378, 382
\raggedbottom ..... 552
\raggedright ... 188, 517
\raisebox ..... 188
\relax .. 12, 28, 131,
    232, 233, 234,
    243, 253, 258,
    305, 314, 318,
    320, 369, 377,
    414, 438, 439,
    441, 442, 514, 524
\renewcommand 83, 84,
    121, 122, 275,
    307, 325, 492,
    496, 500, 504, 508
\renewenvironment .. 242
\repeat ..... 133
\RequirePackage 1, 69,
    70, 71, 81, 82, 93
\RESP@bibliography .
    .... 95, 96, 435
\RESP@bulletboxwidth
    .... 266, 271
\RESP@firstingroupfalse
    .... 461
\RESP@firstingrouptrue
    .... 457,
    463, 467, 471, 475
\RESP@fontautofalse
    .... 15, 18, 21
\RESP@fontautotrue .
    .... 3, 13, 25
\RESP@forthcomingfalse
    .... 64

```

\RESP@forthcomingtrue	65	\scshape	306	\thanks@warning	316
\RESP@linecount	<u>128</u> , 142, 145, 158	\section	<u>492</u>	\thankses	436
\RESP@lsabonfalse	7, 22, 79	\setbox	247, 349	\the ..	132, 234, 235,
\RESP@lsabontrue	16, 19, 79	\setcounter	222, 224	262, 344, 345, 539	
\RESP@manuscriptfalse	55	\setlength	102,	\thefootnote	307, 325
\RESP@manuscripttrue 56		103, 105, 106,		\thepage ..	138, 139, 143
\RESP@mtshadowfalse	9, 38, 87	107, 108, 110,		\thispagestyle	333
\RESP@mtshadowtrue	32, 35, 87	111, 114, 115,		\title	3, 415
\RESP@natbibtrue .. 45		117, 119, 120, 123		\titlenote	4, 296
\RESP@preprintfalse 61		117, 119, 120, 123		\toccontribs	417
\RESP@preprinttrue . 62		\settowidth	267	\toks	342, 344
\RESP@printlinecount	<u>124</u>	\sf@size	<u>422</u>	\toks@	341, 345
\RESP@printlinecountfalse	125	\shortauthors		\topmargin	<u>117</u>
\RESP@printlinecounttrue	126, 127	4, 138, 143, 271,		\trivlist	317
\RESP@rpfontautofalse	31, 34, 37	287, 288, 290,			
\RESP@rpfontautottrue	5, 29, 41	334, 335, 341, 354			
\RESP@screenfalse . 58		\shorttitle			U
\RESP@screentrue .. 59		. 139, 334, 341, 354		\unskip	465,
\RESP@size@warning	46,	\sloppy	547	469, 473, 477, 551	
	49, 50, 51, 52, 53	\Small ..	98, 99, 429, 458		
\RESP@write@paper@info	<u>338</u> , <u>373</u>	\space	245,	\upshape	274
\rightmargin	250	255, 384, 469, 473		\url	171, 478, 534
\rmdefault	90	\splitmaxdepth	545		
\romannumeral	225	\splittopskip	545		
\rpdefault	<u>88</u>	\start@page 192, 223,			
\rpfont	<u>26</u>	225, 379, 386, 400			
\rule	551	\startpage			
		. 5, <u>222</u> , 230, 235			
		\string 295, 384, 386, 539			
		\strut	551		
		\strutbox	545		
		\subjclass	421		
		\subparagraph	<u>508</u>		
		\subsection	<u>496</u>		
		\subsubsection	<u>500</u>		
		\suppresscomma	7		
					V
				\val	10, 26
				\vglue	248
				\volumenumber	<u>5</u> , <u>198</u>
				\vskip	98, 369, 429
				\vtop	247, 360
					W
				\widowpenalty	456
				\write	377, 538
					X
				\xcontribs	417
				\xdef	539
					Y
				\year	262
					Z
				\z@ 188, 224, 249, 251,	
				252, 331, 348,	
				349, 462, 492,	
				496, 500, 504, 551	