

# mynsfc — 国家自然科学基金申请书正文模板\*

Fred Qi†

2015/08/18 发布

摘 要

用于自然科学基金申请书正文部分的撰写。

## 1 使用说明

## 2 实现

```
<*class>
1 %% Options
2 \newif\ifmynsfc@subfig\mynsfc@subfigfalse
3 \DeclareOption{subfig}{\mynsfc@subfigtrue}
4 \ProcessOptions
5 %% Load default class
6 \LoadClass[a4paper,fleqn]{article}

7 %% Load required packages
8 \RequirePackage{titlesec}
9 \RequirePackage{marvosym}
10 \RequirePackage{bm,amsmath,amssymb}
11 \RequirePackage{paralist}
12 \RequirePackage{graphicx}
13 \ifmynsfc@subfig
14 \RequirePackage[config]{subfig}
15 \else
16 \RequirePackage{subcaption}
17 \fi
18 \RequirePackage{xcolor}
19 \RequirePackage{calc}
20 \RequirePackage{hyperref}
21 \hypersetup{%
22   breaklinks=true,
23   colorlinks=true,
24   allcolors=black,
25   pdfpagelabels}
26 \urlstyle{same}

27 %% Load and setup package biblatex
28 \RequirePackage[backend=biber,
29   url=true,
30   isbn=false,
31   defernumbers=true,
32   style=ieee]{biblatex}
33
34 \appto{\bibfont}{\wuhao}
35 \defbibheading{reftype}[\bibname]{\subsection*{#1}}
36 \defbibheading{cvtype}[\bibname]{\paragraph{#1}}
37 \defbibfilter{conference}{type=inproceedings or type=incollection}
```

---

\* 此文档描述的模板版本为 v1.00, 最后修改日期为 2015/08/18.

† E-mail: fred.qi@ieee.org

```

38
39 \RequirePackage{xpatch}% or use http://tex.stackexchange.com/a/40705
40
41 \newbibmacro*{name:bold}[2]{%
42   \def\do##1{\ifstrequal{#1, #2}{##1}{\bfseries\listbreak}}}%
43   \dolistloop{\boldnames}
44 \newcommand*{\boldnames}{}
45
46 \xpretobibmacro{name:last}{\begingroup\usebibmacro{name:bold}{#1}{#2}}{}{}
47 \xpretobibmacro{name:first-last}{\begingroup\usebibmacro{name:bold}{#1}{#2}}{}{}
48 \xpretobibmacro{name:last-first}{\begingroup\usebibmacro{name:bold}{#1}{#2}}{}{}
49 \xpretobibmacro{name:delim}{\begingroup\normalfont}}{}{}
50
51 \xapptobibmacro{name:last}{\endgroup}}{}{}
52 \xapptobibmacro{name:first-last}{\endgroup}}{}{}
53 \xapptobibmacro{name:last-first}{\endgroup}}{}{}
54 \xapptobibmacro{name:delim}{\endgroup}}{}{}

```

`\dummyMacro` This is a dummy macro. If it did anything, we'd describe its implementation here.

```

55 %   \begin{macrocode}
56 %
57 \newcommand{\dummyMacro}{}

58 %% Setup Chinese fonts with xeCJK
59 \RequirePackage[AutoFakeBold]{xeCJK}
60 \def\CJK@null{\kern\CJKnullspace\Unicode{48}{7}\kern\CJKnullspace}
61 \punctstyle{quanjiao}
62 \defaultfontfeatures{Mapping=tex-text} % after fontspec
63 \setCJKmainfont{仿宋_GB2312}
64 \setCJKsansfont{SimHei}
65 \setCJKfamilyfont{song}{仿宋_GB2312}
66 \setCJKfamilyfont{hei}{SimHei}
67 \setCJKfamilyfont{kai}{KaiTi}
68 \setmainfont{Times New Roman}
69 \setmonofont{Courier Std}

```

```

\kai Define commands to select Chinese fonts.
\kaiti
\song
\songti
\hei
\heiti

70 \newcommand{\kai}{\CJKfamily{kai}} % 仿宋体
71 \newcommand{\song}{\CJKfamily{song}} % 宋体
72 \newcommand{\hei}{\CJKfamily{hei}} % 黑体
73 \def\kaiti{\kai}
74 \def\songti{\song}
75 \def\heiti{\hei}

76 \newlength\mysf@linespace
77 \newcommand{\mysf@choosefont}[2]{%
78   \setlength{\mysf@linespace}{#2*\real{#1}}%
79   \fontsize{#2}{\mysf@linespace}\selectfont}
80 \def\mysf@define@fontsize#1#2{%
81   \expandafter\newcommand\csname #1\endcsname[1][\baselinestretch]{%
82     \mysf@choosefont{##1}{#2}}
83 \mysf@define@fontsize{chuhao}{42bp}
84 \mysf@define@fontsize{xiaochu}{36bp}
85 \mysf@define@fontsize{yihao}{26bp}
86 \mysf@define@fontsize{xiaoyi}{24bp}
87 \mysf@define@fontsize{erhao}{22bp}
88 \mysf@define@fontsize{xiaoer}{18bp}
89 \mysf@define@fontsize{sanhao}{16bp}
90 \mysf@define@fontsize{xiaosan}{15bp}
91 \mysf@define@fontsize{sihao}{14bp}
92 \mysf@define@fontsize{banxiaosi}{13bp}
93 \mysf@define@fontsize{xiaosi}{12bp}
94 \mysf@define@fontsize{dawu}{11bp}
95 \mysf@define@fontsize{wuhao}{10.5bp}

```

```

96 \mysnfc@define@fontsize{xiaowu}{9bp}
97 \mysnfc@define@fontsize{liuhao}{7.5bp}
98 \mysnfc@define@fontsize{xiaoliu}{6.5bp}
99 \mysnfc@define@fontsize{qihao}{5.5bp}
100 \mysnfc@define@fontsize{bahao}{5bp}

101 % Define page layout
102 \setlength{\textwidth}{\paperwidth}
103 \setlength{\textheight}{\paperheight}
104 \setlength\marginparwidth{0mm}
105 \setlength\marginparsep{0mm}
106 \addtolength{\textwidth}{-50mm}
107 \setlength{\oddsidemargin}{0mm}
108 \setlength{\evensidemargin}{\oddsidemargin}
109 \setlength{\headheight}{20pt}
110 \setlength{\topskip}{0mm}
111 \setlength{\skip\footins}{15pt}
112 \setlength{\topmargin}{-15mm}
113 \setlength{\footskip}{13mm}
114 \setlength{\headsep}{6mm}
115 \addtolength{\textheight}{-50mm}
116 \setlength{\parskip}{0pt \@plus2pt \@minus0pt}

```

`\normalsize` Redefine command

```

117 \renewcommand\normalsize{%
118   \@setfontsize\normalsize{12bp}{20bp}
119   \abovedisplayskip=10bp \@plus 2bp \@minus 2bp
120   \abovedisplayshortskip=10bp \@plus 2bp \@minus 2bp
121   \belowdisplayskip=\abovedisplayskip
122   \belowdisplayshortskip=\abovedisplayshortskip}

```

```

123 % Define page styles
124 \def\ps@mysnfc@empty{%
125   \let\@oddhead\@empty%
126   \let\@evenhead\@empty%
127   \let\@oddfoot\@empty%
128   \let\@evenfoot\@empty}

```

`hcomment` Dimmed text used as hint after section titles.

```

129 \newenvironment{hcomment}{\vskip-3pt\color{gray}}{\vskip6pt}

```

`\figurename` Translate English to Chinese.

```

\tablename 130 \renewcommand{\figurename}{图}
\contentsname 131 \renewcommand{\tablename}{表}
132 \renewcommand{\contentsname}{内容目录}

```

```

133 %
134 \DeclareCaptionLabelFormat{mysnfc@cap}{\wuhao#1\rmfamily#2}
135 \DeclareCaptionLabelSeparator{mysnfc@sep}{\hspace{1em}}
136 \DeclareCaptionFont{mysnfc@capfont}{\wuhao}
137 \captionsetup{labelformat=mysnfc@cap,
138               labelsep=mysnfc@sep,
139               font=mysnfc@capfont,
140               justification=centering}

```

`CJKindent` Indent with two Chinese full spaces.

```

141 %
142 \newlength\mysnfc@CJK@twochars
143 \newcommand{\mysnfc@unicode}[2]{\char\numexpr#1*256+#2\relax}
144 \def\mysnfc@CJK@space{\mysnfc@unicode{48}{7}}
145 \def\CJKindent{%
146   \settowidth\mysnfc@CJK@twochars{\mysnfc@CJK@space\mysnfc@CJK@space}%
147   \parindent\mysnfc@CJK@twochars}

```

```

\part      ommands to format several levels of titles (part, section, subsection).
\section   148 \def\nsfc@CJKnumber#1{\ifcase#1{零}\or%
\subsection 149  {一}\or{二}\or{三}\or{四}\or{五}\or%
\subsubsection 150  {六}\or{七}\or{八}\or{九}\or{十}\or%
C          151  {十一}\or{十二}\or{十三}\or{十四}\or{十五}\or%
          152  {十六}\or{十七}\or{十八}\or{十九}\or{二十}\fi}
          153
          154 \renewcommand{\thepart}{\nsfc@CJKnumber{\c@part}}
          155 \titleformat{\part}{\kai\bfseries\sanhao}%
          156      {(\thepart)}{0ex}{ }
          157 \titlespacing{\part}{0ex}{4ex}{2ex}
          158
          159 \@addtoreset{section}{part}
          160 \renewcommand{\thesection}{\arabic{section}.}
          161 \titleformat{\section}{\kai\bfseries\xiaosan}%
          162      {\thesection}{0.25em}{ }
          163 \titlespacing{\section}{0em}{4ex}{2ex}
          164
          165 \renewcommand{\thesubsection}{\bf\arabic{section}.\arabic{subsection}}
          166 \titleformat{\subsection}{\hei\sihao}%
          167      {\thesubsection}{0.25em}{ }
          168 \titlespacing{\subsection}{0em}{2ex}{1ex}
          169
          170 \titleformat{\subsubsection}{\kaiti\bfseries\banxiaosi}%
          171      {\thesubsubsection}{0.25em}{ }
          172 \titlespacing{\subsubsection}{0em}{2ex}{1ex}

          173 \let\mysfc@begindocumenthook\@begindocumenthook
          174 \let\mysfc@enddocumenthook\@enddocumenthook
          175 \def\AtBeginDocument{\g@addto@macro\mysfc@begindocumenthook}
          176 \def\AtEndDocument{\g@addto@macro\mysfc@enddocumenthook}
          177 \def\@begindocumenthook{\mysfc@begindocumenthook}
          178 \def\@enddocumenthook{\mysfc@enddocumenthook}
          179 \AtBeginDocument{\ps@mysfc@empty\CJKindent}
          180 \endinput
          181 \endclass

```

### 3 Change History

v1.00  
 General: First public release . . . . . 1

### 4 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in **roman** refer to the code lines where the entry is used.

<b>Symbols</b>	\@plus . . . . . 116, 119, 120	\AtEndDocument . . . . . 176
\@addtoreset . . . . . 159	\@setfontsize . . . . . 118	
\@begindocumenthook . . . . . 173, 177		<b>B</b>
\@empty . 125, 126, 127, 128	<b>A</b>	\banxiaosi . . . . . 170
\@enddocumenthook . . . . . 174, 178	\abovedisplayshortskip . . . . . 120, 122	\baselinestretch . . . 81
\@evenfoot . . . . . 128	\abovedisplayshortskip . . . . . 119, 121	\begin . . . . . 55
\@evenhead . . . . . 126	\addtolength . . . 106, 115	\begingroup 46, 47, 48, 49
\@minus . . . . 116, 119, 120	\appto . . . . . 34	\belowdisplayshortskip . . . . . 122
\@oddfoot . . . . . 127	\arabic . . . . . 160, 165	\belowdisplayskip . 121
\@oddhead . . . . . 125	\AtBeginDocument 175, 179	\bf . . . . . 165
		\bfseries 42, 155, 161, 170

<code>\bibfont</code> .....	34	<b>I</b>	<code>\real</code> .....	78	
<code>\bibname</code> .....	35, 36	<code>\ifcase</code> .....	148	<code>\relax</code> .....	143
<code>\boldnames</code> .....	43, 44	<code>\ifmynsfc@subfig</code> .	2, 13	<code>\renewcommand</code> 117, 130,	
<b>C</b>		<code>\ifstrequal</code> .....	42	131, 132, 154, 160, 165	
<code>\C</code> .....	148	<b>K</b>	<code>\RequirePackage</code> ...		
<code>\c@part</code> .....	154	<code>\kai</code> .....	70, 155, 161	8, 9, 10, 11, 12, 14,	
<code>\captionsetup</code> .....	137	<code>\kaiti</code> .....	70, 170	16, 18, 19, 20, 28, 39, 59	
<code>\char</code> .....	143	<code>\kern</code> .....	60	<code>\rmfamily</code> .....	134
<code>\CJK@null</code> .....	60	<b>L</b>		<b>S</b>	
<code>\CJKfamily</code> ....	70, 71, 72	<code>\let</code> .....	125,	<code>\sanhao</code> .....	155
<code>\CJKindent</code> .	141, 145, 179	126, 127, 128, 173, 174		<code>\section</code> .....	148
<code>\CJKnullspace</code> .....	60	<code>\listbreak</code> .....	42	<code>\selectfont</code> .....	79
<code>\color</code> .....	129	<code>\LoadClass</code> .....	6	<code>\setCJKfamilyfont</code> .	
<code>\contentsname</code> .....	130	<b>M</b>		..... 65, 66, 67	
<code>\csname</code> .....	81	<code>\marginparsep</code> .....	105	<code>\setCJKmainfont</code> ....	63
<b>D</b>		<code>\marginparwidth</code> ...	104	<code>\setCJKsansfont</code> ....	64
<code>\DeclareCaptionFont</code> 136		<code>\mynsfc@begindocumenthook</code>		<code>\setlength</code> .....	78,
<code>\DeclareCaptionLabelFormat</code>		..... 102, 103, 104, 105,		107, 108, 109, 110,	
..... 134		<code>\mynsfc@choosefont</code>		111, 112, 113, 114, 116	
<code>\DeclareCaptionLabelSeparation</code>		..... 77, 82		<code>\setmainfont</code> .....	68
..... 135		<code>\mynsfc@CJK@space</code> .		<code>\setmonofont</code> .....	69
<code>\DeclareOption</code> .....	3	..... 144, 146		<code>\settowidth</code> .....	146
<code>\def</code> ....	42, 60, 73, 74,	<code>\mynsfc@CJK@twochars</code>		<code>\sihao</code> .....	166
75, 80, 124, 144, 145,		..... 142, 146, 147		<code>\skip</code> .....	111
148, 175, 176, 177, 178		<code>\mynsfc@define@fontsize</code>		<code>\song</code> .....	70
<code>\defaultfontfeatures</code>		..... 80, 83, 84,		<code>\songti</code> .....	70
..... 62		85, 86, 87, 88, 89,		<code>\subsection</code> ....	35, 148
<code>\defbibfilter</code> .....	37	90, 91, 92, 93, 94,		<code>\subsubsection</code> ....	148
<code>\defbibheading</code> ..	35, 36	95, 96, 97, 98, 99, 100		<b>T</b>	
<code>\do</code> .....	42	<code>\mynsfc@enddocumenthook</code>		<code>\tablename</code> .....	130
<code>\dolistloop</code> .....	43	..... 174, 176, 178		<code>\textheight</code> ....	103, 115
<code>\dummyMacro</code> .....	55	<code>\mynsfc@linespace</code> .		<code>\textwidth</code> .....	102, 106
<b>E</b>		..... 76, 78, 79		<code>\thepart</code> .....	154, 156
<code>\else</code> .....	15	<code>\mynsfc@subfigfalse</code> .	2	<code>\thesection</code> ....	160, 162
<code>\endcsname</code> .....	81	<code>\mynsfc@subfigtrue</code> ..	3	<code>\thesubsection</code> .	165, 167
<code>\endgroup</code> ..	51, 52, 53, 54	<code>\mynsfc@unicode</code> 143, 144		<code>\thesubsubsection</code> .	171
<code>\endinput</code> .....	180	<b>N</b>		<code>\titleformat</code> .....	
environments:		<code>\newbibmacro</code> .....	41	..... 155, 161, 166, 170	
<code>hcomment</code> .....	129	<code>\newif</code> .....	2	<code>\titlespacing</code> .....	
<code>evensidemargin</code> ...	108	<code>\newlength</code> .....	76, 142	..... 157, 163, 168, 172	
<code>expandafter</code> .....	81	<code>\normalfont</code> .....	49	<code>\topmargin</code> .....	112
<b>F</b>		<code>\normalsize</code> .....	117	<code>\topskip</code> .....	110
<code>\fi</code> .....	17, 152	<code>\nsfc@CJKnumber</code> 148, 154		<b>U</b>	
<code>\figurename</code> .....	130	<code>\numexpr</code> .....	143	<code>\Unicode</code> .....	60
<code>\fontsize</code> .....	79	<b>O</b>		<code>\urlstyle</code> .....	26
<code>\footins</code> .....	111	<code>\oddsidemargin</code> .	107, 108	<code>\usebibmacro</code> ..	46, 47, 48
<code>\footskip</code> .....	113	<code>\or</code> ..	148, 149, 150, 151, 152	<b>V</b>	
<b>G</b>		<b>P</b>		<code>\vskip</code> .....	129
<code>\g@addto@macro</code> .	175, 176	<code>\paperheight</code> .....	103	<b>W</b>	
<b>H</b>		<code>\paperwidth</code> .....	102	<code>\wuhao</code> .....	34, 134, 136
<code>hcomment (environment)</code> 129		<code>\paragraph</code> .....	36	<b>X</b>	
<code>\headheight</code> .....	109	<code>\parindent</code> .....	147	<code>\xapptobibmacro</code> ...	
<code>\headsep</code> .....	114	<code>\parskip</code> .....	116	..... 51, 52, 53, 54	
<code>\hei</code> .....	70, 166	<code>\part</code> .....	148	<code>\xiaosan</code> .....	161
<code>\heiti</code> .....	70	<code>\ProcessOptions</code> ....	4	<code>\xpretobibmacro</code> ...	
<code>\hspace</code> .....	135	<code>\ps@mynsfc@empty</code> 124, 179		..... 46, 47, 48, 49	
<code>\hypersetup</code> .....	21	<code>\punctstyle</code> .....	61		